



By Orthene.

Orthene Chemicals Ltd is approved to ISO/TS 16949
Certificate No: LRQ 0964114

Halo By Orthene
BREMBER ROAD, SOUTH HARROW INDUSTRIAL ESTATE
HARROW, MIDDLESEX, HA2 8UJ, UK
TEL: +44 (0)20 8864 4414

Halo P1 Technical Data Sheet

Product: HALO P1
Specification No: OSS 192
Issue No: 3
Date: January 2024

Halo P1 specialist racing brake fluid is developed for the highest level, and most demanding professional motor racing series.

Halo P1 is formulated using the purest form of methyl borate ester which gives the fluid an extremely high polarity and ensures low compressibility across a wide temperature range and delivers a more consistent pedal feel over an entire race distance.

Test Required	Typical Results	Specification
Dry Equilibrium Reflux Boiling Point, °C	341°C, 646°F	338°C, 658°F Min.
Wet Equilibrium Reflux Boiling Point, °C	206°C, 403°F	200°C, 392°F Min.
Kinematic Viscosity @ -40 °C, cSt	1400	-
Kinematic Viscosity @ 100 °C, cSt	2.63	1.5 cSt Min.
pH	6.60	-

Notes:

- Halo P1 is for track use only
- Borate Glycol ether ester formulation
- Compatible with conventional and ABS brake systems

Additional technical data available on request: info@halobyorthene.com

Issued By: Dan Stafford, Chief Development Chemist, Motorsport